Certificate Number UL-US-L79070-341911-42902891-2

Report Reference E79070-19820924

Date 24-Oct-2023

Issued to: Topworx Inc

3300 Fern Valley Rd Louisville, KY 40213-3528

United States

This is to certify that representative samples of

NOIV - Auxiliary Devices for Use in Hazardous Locations

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the

Standard(s) indicated on this Certificate.

Standard(s) for Safety: UL 1203, Edition 5, Issued 2013-11-22, Revised 2022-04-

05

Additional Information: See the UL Online Certifications Directory at

https://iq.ulprospector.com for additional information

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.

Deborah Jennings-Conner, VP Regulatory Services

U

Certificate Number UL-US-L79070-341911-42902891-2

Report Reference E79070-19820924

Date 24-Oct-2023

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

Model	Category Description
527-003-430	Proximity Switches
527-003-430	Proximity Switches
527-003-431	Proximity Switches
570-999-130	Proximity Switches
570-999-130	Proximity Switches
71, 71M, 73, 73M, 75, 75M, 77, 7G, 7GM and 7I, followed by 1 or 2, followed by 3, 4, 5 or 6, followed by 5, followed by 2 or 6, followed by 5, followed by letters and/or numbers.	Proximity Switches
71, 71M, 73, 73M, 75, 75M, , 77, 7G, 7GM and 7I followed by 1 or 2, followed by 3, 4, 5, or 6, followed by 5, followed by 2 or 6, followed by 3 or 4, followed by letters and/or numbers.	Auxiliary Devices for HazLoc
73, 73M, 75, 75M, and 77, followed by 1, followed by 3, followed by 5, followed by 2 or 6, followed by K or R, followed by F, followed by 1-4 numbers. Suitable for High Ambient Temperature.	Proximity Switches
7527-007-081	Proximity Switches
7527-007-081	Proximity Switches
7CX or 7DX, followed by 4, 7 or 8, followed by 3, 4 or 5, followed by 5, followed by 5 or 6, followed by 5, followed by letters and/or numbers	Proximity Switches
7CX or 7DX, followed by 4, 7 or 8, followed by 3, 4 or 5, followed by 5, followed by 5 or 6, followed by D, 3 or 4, followed by letters and/or numbers	Proximity Switches
7G, 7GM, 7I, 71, 71M, 73, 73M, 75, 75M, 77, followed by 1 or 2, followed by 3, 4, 5 or 6, followed by 5, followed by 2 or 6, followed by 3, followed by letters and/or numbers or 71M-16523.	Proximity Switches
7G and 7GM, followed by 1 or 2, followed by 3, followed by 5, followed by 2 or 6, followed by K or R, followed by F, followed by 1-4 numbers. Suitable for High Ambient Temperature.	Proximity Switches
7J, followed by 1, followed by 3, followed by 5, followed by 2 or 6, followed by 5, followed by J, followed by S, followed by M or P	Proximity Switches
7J, followed by 1, followed by 3, followed by 5, followed by 2 or 6, followed by D, 3 or 4, followed by J, followed by S, followed by M or P	Proximity Switches

Olbrah Jennings-Corne



Certificate Number UL-US-L79070-341911-42902891-2

Report Reference E79070-19820924

Date 24-Oct-2023

95LX, followed by 1 to 5, followed by B2 to B6, followed by A or any 8-position alphanumeric designation	Proximity Switches
TW557745	Proximity Switches

Debrah Jenning - Course

Deborah Jennings-Conner, VP Regulatory Services

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at https://ul.com/aboutul/locations/



Certificate Number UL-CA-L79070-352611-42902891-1

Report Reference E79070-19820924

Date 24-Oct-2023

Issued to: Topworx Inc

3300 Fern Valley Rd Louisville, KY 40213-3528

United States

This is to certify that NWFN7 - Auxiliary Devices for Use in Zone Classified representative samples of Hazardous Locations Certified for Canada

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the

Standard(s) indicated on this Certificate.

Standard(s) for Safety: CSA C22.2 NO. 60079-0:19, 4th Ed., Issue Date: 2019-02-

01, CSA C22.2 No. 60079-1, Edition 2, Issued 2011-12-01, CSA C22.2 No. 60079-11, Edition 2, Issued 2014-02-01, CSA C22.2 No. 60079-31, Edition 1, Issued 2012-01-01

Additional Information: See the UL Online Certifications Directory at

https://ig.ulprospector.com for additional information

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.

Deborah Jennings-Conner, VP Regulatory Services

UL LLC





Certificate Number UL-CA-L79070-352611-42902891-1

Report Reference E79070-19820924

Date 24-Oct-2023

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

Model	Category Description
71, 71M, 73, 75, 77, 7G and 7I, may be followed by M,	Proximity Switches
followed by 1 or 2, followed by 3, 4, 5 or 6, followed by 5,	Jr)(Ur)(Ur)(Ur)(Ur)(Ur)(
followed by 2, 3, 4 or 6, followed by D or 9, followed by letters and/or numbers, may be followed by Z.	
71, 71M, 73, 73M, 75, 75M, 77, 7G, 7GM and 7I,	Proximity Switches, Accordance
followed by 1 or 2, followed by 3, 4, 5 or 6, followed by 5,	1 Toximity Ownones, Accordance
followed by 2 or 6, followed by L, F, G or H, followed by	
letters and/or numbers, followed by Z.	\times \times \times \times \times
7CX or 7DX, followed by 4, 7 or 8, followed by 3, 4 or 5,	Proximity Switches, Accordance
followed by 5, followed by 5 or 6, followed by L, F, G or	LVALVALVALVALVA
H, followed by letters and/or numbers, followed by Z.	
7CX or 7DX, followed by 4, 7 or 8, followed by 3, 4 or 5,	Proximity Switches
followed by 5, followed by 5, followed by D or 9, followed	'L M UL M UL M UL M UL M I
by letters and/or numbers, may be followed by Z.	
7J, followed by 1, followed by 3, followed by 5, followed	Proximity Switches, Accordance
by 2 or 6, followed by L, F, G or H, followed by J,	1. 3/ 0. 3/ 0. 3/ 0. 3/ 0. 3/
followed by S, followed by M or P, followed by Z.	TVATVATVATV
7J or 7JM, followed by 1, followed by 3, followed by 5,	Proximity Switches
followed by 2 or 6, followed by D or 9, may be followed	ı. Vii. Vii. Vii. Vii. Vi
by Z	

Olbrah Jennings-Course

Deborah Jennings-Conner, VP Regulatory Services

UL LLC



Certificate Number UL-CA-L79070-342211-42902891-1

Report Reference E79070-19820924

Date 24-Oct-2023

Issued to: Topworx Inc

3300 Fern Valley Rd Louisville, KY 40213-3528

United States

This is to certify that representative samples of

NOIV7 - Auxiliary Devices for Use in Hazardous Locations

Certified for Canada

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the

Standard(s) indicated on this Certificate.

Standard(s) for Safety: CSA C22.2 No. 30, Edition 4, Issued 2020-04-01, CSA

C22.2 No. 25, Edition 1, Issued 1966-09-01

Additional Information: See the UL Online Certifications Directory at

https://ig.ulprospector.com for additional information

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.

Deborah Jennings-Conner, VP Regulatory Services

(II)

Certificate Number UL-CA-L79070-342211-42902891-1

Report Reference E79070-19820924

Date 24-Oct-2023

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

Model	Category Description
527-003-430	Proximity Switches
527-003-430	Proximity Switches
527-003-431	Proximity Switches
570-999-130	Proximity Switches
570-999-130	Proximity Switches
71, 71M, 73, 73M, 75, 75M, 77, 7G, 7GM and 7I, followed by 1 or 2, followed by 3, 4, 5 or 6, followed by 5, followed by 2 or 6, followed by D, 3, or 4, followed by letters and/or numbers.	Proximity Switches
71, 71M, 73, 73M, 75, 75M, 77, 7G, 7GM and 7I, followed by 1 or 2, followed by 3, 4, 5 or 6, followed by 5, followed by 2 or 6, followed by 5, followed by letters and/or numbers.	Proximity Switches
73, 73M, 75, 75M, and 77, followed by 1, followed by 3, followed by 5, followed by 2 or 6, followed by K or R, followed by F, followed by 1-4 numbers. Suitable for High Ambient Temperature.	Proximity Switches
7527-007-081	Proximity Switches
7527-007-081	Proximity Switches
7CX or 7DX, followed by 4, 7 or 8, followed by 3, 4 or 5, followed by 5, followed by 5 or 6, followed by 4, followed by letters and/or numbers	Proximity Switches
7CX or 7DX, followed by 4, 7 or 8, followed by 3, 4 or 5, followed by 5, followed by 5 or 6, followed by 5, followed by letters and/or numbers	Proximity Switches
7G and 7GM, followed by 1 or 2, followed by 3, followed by 5, followed by 2 or 6, followed by K or R, followed by F, followed by 1-4 numbers. Suitable for High Ambient Temperature.	Proximity Switches
7J, followed by 1, followed by 3, followed by 5, followed by 2 or 6, followed by 5, followed by J, followed by S, followed by M or P	Proximity Switches
7J, followed by 1, followed by 3, followed by 5, followed by 2 or 6, followed by D or 4, followed by J, followed by S, followed by M or P	Proximity Switches
95LX, followed by 1 to 5, followed by B2 to B6, followed by A or any 8-position alphanumeric designation	Proximity Switches
TW557745	Proximity Switches

Octoah Jenning-Course

(UL)

eborah Jennings-Conner, VP Regulatory Services